

Cluster Layout

Blackrock network

RedHead

3com VLAN 1

High Performance Computing with Configuration Management



Team: Evan Leeseberg, James Kang, Katherine Nystrom Mentors: Kevin Tegtmeier, Andree Jacobson, Carolyn Connor

Abstract

This research project investigated the Cfengine and Puppet configuration management tools and evaluated their strengths and weaknesses. Each configuration management tool was implemented on separate Virtual Local Area Networks (VLANs) and run on designated servers to manage their respective nodes. Cfengine is currently used on LANL clusters, and Puppet is being considered for use on future clusters.

Goals

- Analyze two configuration management tools.
- Determine whether Puppet is a viable replacement for Cfengine.
- Create Puppet/Cfengine configuration files capable of completely reinstalling the Puppet and Cfengine head nodes.

Why Configuration Management?

- Number of cluster nodes is increasing—not practical to configure everything manually
- Important to build nodes quickly and correctly
- Prevents system drift configuration differing across nodes

 Implementation Issues
- Documentation incomplete, contained errors, vague
- Bootstrapping implementation not straight-forward

Summary

- Puppet is a viable alternative to Cfengine.
- Cfengine has a mature user base and ample documentation. Puppet is relatively new and gaining popularity. Puppet is supported by an open development community.
- We were able to net boot cluster nodes, use Puppet or Cfengine to configure them and reintegrate them into the cluster within minutes.

This is a diagram of our cluster. Using Virtual Local Area Networks allowed us to simulate having two clusters even though all the machines are connected to the same switch.




Front view of cluster




Back view of cluster

Cfengine vs. Puppet



- All Puppet and Cfengine configuration files and system configuration files were managed with Subversion
- The Staging and Working directories are checked out copies from the database
- Working directory used for all editing
- After an edit the file is checked back into the database and manually copied to the Test directory
- Staging directory holds the current production copies of files
- Files are copied from Staging to the Live directory.



Subversion

Contact Information:

Evan Leeseberg
elleeseb@mtu.edu
Michigan Technological
University

James Kang jkang@unm.edu University of New Mexico

Katherine Nystrom
knystro1@unm.edu
University of New Mexico







